
Performance Curve



Power pack - GHPU30

Engine : John Deere 4045TF290 (72.4 HP @ 2400 rpm)		
Engine speed	2400 rpm	
Hydraulic motor	Gear type	
Hydraulic pump displacement	3.6 cu. in.	
Output flow	32 USGPM	
Wet weight	3,349 lbs	
Hydraulic reservoir capacity	40 US Gallons	

Power pack dimensions

Length	119 "
Width	66 "
Height	77 "

Hydraulic Hose

Feed/Return	1" Male Hydraulic Fitting x 1" Female Hydraulic Fitting with Wingnuts
Bleed Line	1/2" Hydraulic Quick Connect x 1/2" Hydraulic Quick Connect

Maximum hose lengths

		-,		
Engine (rpm)	2000	2200	2400	2600
Max Length (feet)	131	115	98	66

Materials

Pump casing & suction cover	Cast iron to BS1452 Grade 220.
Wearplates	Rear - Cast iron BS1452 Gr220 Front - Hard iron
Pump Shaft	Carbon Steel BS 970-3:1991 080M40
Impeller	Hard Iron
Mechanical Seal Face	Silicon Carbide vs Silicon Carbide
Suction Strainer and Lifting Bracket	Fabrication Mild Steel tube and plate.

Pump end

Drive pressure	3500 psi
Pump speed	2178 rpm
Hydraulic motor	Gear type
Hydraulic motor displacement	3.0 cu. in.
Flow	32 USGPM
Wet Weight	386 lbs

Pump end dimensions

Length	23"
Width	18"
Height	32"

Great Pumps. Great People.®

Performance data provided in tables is based on water tests at sea level and 68°F ambient. All information is approximate and for general guidance only. Please contact the factory or office for further details.

Reference number: 95-1225-3000 Date of issue :

March 15, 2012

Home Office Godwin Pumps of America, Inc. 84 Floodgate Road Bridgeport, NJ 08014 USA (856) 467-3636 . Fax (856) 467-4841 Email: sales@godwinpumps.com



